

System And Method For Detecting And Jamming Emitter Signals GOUNALIS, Anthony J. Serial No.: 10/675,540




FIG. 3

. 1			Emitter Database 401	Emit Ent <i>40</i>	ry
1		Emitter	Parameters		
	Emitter Model	Dwell Solution(s)	Constraints	Rules	
			•		
			•		
			•		
					
N					







FIG. 5


System And Method For Detecting And Jamming Emitter Signals


GOUNALIS, Anthony J. Serial No.: 10/675,540

















Min MDT (ms)	3	5	2	4
RF Max (MHz)	1300	1350	1810	1860
RF Min (MHz)	1000	1220	1510	1730
Detecting Method 2 30MHz IF/ 15MHz VBW RVT	650 ms	780 ms	330 ms	390 ms
Detecting Method 1 250MHz IF/ 15MHz VBW RVT	100 ms	120 ms	110 ms,	130 ms
Emitter Name	E1	E2	E3	E4

(

		1 1 1 1 0			0		C coitile	7	Total	cost 31/650 ≈ .048	
1250]	0 1270	Dwell 9	DD Max 5	RVTMin	650	+ Cost = 5/650	
					1210 1240	Dwell 8	DD _{Мах} 5	RVT _{Min}	650	+ Cost + 5/650	
	:				1180 12	Dwell 7	DD Max	RVTMin	650	+ Cost + 3/650	
				05	1150 11	Dwell 6	DD Max	RVT _{Min}	650	+ Cost 3/650	
	Dwell 1	$DD_{Max} = 5$	$RVT_{Min} = 100$	Cost = 5/100 = .05	1120 11	Dwell 5	DD Max	RVTMin	650	+ Cost 3/650	
		DD _M	RVT	Cost :	1090 11	Dwell 4	DD Max	RVTMin	650	+ Cost 3/650	
						1060	Dwell 3	DD Max	RVTMin	650	+ Cost 3/650
					1030 10	Dwell 2	DD Max	RVTMin	650	+ Cost 3/650	
0001					1000	Dwell 1	DD Max	RVTMin	650	Cost 3/650	
_					-						

FIG. 14A

1510								1760	
			Ó	Dwell 1					
			DD _{Mc}	$DD_{Max} = 4 \text{ ms}$	Ø				1 1 1 1 0
			RVTM	$RVT_{Min} = 330 \text{ ms}$	SE.				Solution
			Cost =	Cost = $4/330 = .01\overline{2}$	012			ן	
1510	1540 15	1570 16	1600 1630		1660 16	1690 17	1720 1750	0 1780	
Dwell 1	1 Dwell 2	Dwell 3	Dwell 4	Dwell 5	Dwell 6	Dwell 7	Dwell 8	Dwell 9	
DD Max	DD Max	DD _{Max}	DD Max	DD Max	DD Max	DD Max	DD Max	DD _{Max}	Solution 2
RVT _{Min} 330 ms	RVTMin	RVT _{Min} 330 ms	RVT _{Min} 330 ms	RVT _{Min} 330 ms	RVT _{Min} 330 ms	RVT _{Min} 330 ms	RVT _{Min} 330 ms	RVT _{Min} 330 ms	
Cost	Cost + Cost + Cost	+ Cost +	+ Cost +	+ Cost +	+ Cost + Cost + Cost + Cost	- Cost +	Cost +	٦ "	$22/330 = .0\overline{6}$

FIG. 14B




FIG. 15




FIG. 16

Name	RF Min	RF Max		
E1	1100	1200		
E2	1150	1250		




FIG. 17





FIG. 18

Emitter	Dwell Duration (ms)	Revisit Time (ms)
Emitter 1	1	500
Emitter 2	2	1200

FIG. 19

Emitter	Dwell Duration (ms)	Revisit Time (ms)	Cost
Emitter 1	1	500	.002
Emitter 2	5	1000	.005

FIG. 20



System And Method For Detecting And Jamming Emitter Signals GOUNALIS, Anthony J. Serial No.: 10/675,540




FIG. 22





FIG. 23

							- 9051	— 9052			
9044			RVT	200	700	800	2000	2868			740
,	1	Data	EDT	7	6	=	19	17			FIG 24C
			MDT	-	2	2.3	3	3.05			FIC
9044							-9048	9049	— 9050		
	1		RVT	200	700	800	1000	2000	2000	2868	4R
		Data	EDT	7	6	11	3.5	19	19	17	FIC 24R
			TOM	1	2	2.3	0.5	3	3	3.05	FIG
9044											
`	1		RVT	2868	2000	2000	200	700	800	1000	44
		Data	EDT	17	19	19	7	6	11	3.5	FIG 24
			MDT	3.05	3	3	-	7	2.3	0.5	FIG

System And Method For Detecting And Jamming Emitter Signals GOUNALIS, Anthony J. Serial No.: 10/675,540



System And Method For Detecting And Jamming Emitter Signals GOUNALIS, Anthony J. Serial No.: 10/675,540




FIG. 25




FIG. 26

System And Method For Detecting And Jamming Emitter Signals GOUNALIS, Anthony J. Serial No.: 10/675,540





FIG. 27

System And Method For Detecting And Jamming Emitter Signals GOUNALIS, Anthony J. Serial No.: 10/675,540






FIG. 29

System And Method For Detecting And Jamming Emitter Signals GOUNALIS, Anthony J. Serial No.: 10/675,540




FIG. 30

